



PRODUCT CATALOGUE 2025



Excellence in Biometric Solutions and Beyond

Realtime Biometrics has established itself as a trusted leader in biometric systems, security technology, and management software. From humble beginnings, we have grown into a dynamic organization that seamlessly integrates hardware and software solution to meet the diverse need of businesses across industries. We've successfully partnered with organizations across industries, helping them improve productivity, security, and operational efficiency. As we move forward, our vision is to continue advancing in biometric and management technologies while maintaining a strong commitment to quality, customer satisfaction and innovation.

Software Expertise

We offer a suite of intelligent management software that simplifies operations and enhances efficiency attendance and payroll management, Gym management, Visitor Management, Canteen Management

Hardware Expertise

Biometric Attendance Systems, Face and Fingerprint Aadhaar Based Attendance, Smart Cameras, Parking Barriers, Door Frame Metal Detectors, Hand Held Meter Detector, Accessories, Smart Door Lock, Power over Ethernet (PoE)

Certificates



INDIA



UNITED STATES OF AMERICA



UNITED KINGDOM



EUROPE



(CE) Certificate



(ISO) Certificate




(RoHS) Certificate



(BIS) Certificate

Realtime C101


- Fingerprint Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **50000**
- Display Size : **2.6 Inch**
- Communication : **USB Disk**
- **Finger + Card (USB Connect Excel Report)**
- Adapter : **5V 1amp**



Attendance and Access Control


Realtime C101+

- Fingerprint Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **50000**
- Display Size : **2.6 Inch**
- Access Control : **Yes**
- Communication : **USB Disk**
- Adapter : **12v**



Realtime RS 9n

- Fingerprint Capacity : **1200**
- Card Capacity : **1200**
- Password Capacity : **1200**
- Attendance logs : **100000**
- Display Size : **2.6 Inch**
- Access Control : **Yes**
- Wiegand In/Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime RS 9w

- Fingerprint Capacity : **1200**
- Card Capacity : **1200**
- Password Capacity : **1200**
- Attendance logs : **100000**
- Display Size : **2.6 Inch**
- Access Control : **Yes**
- Wiegand In/Out : **Supported**
- Support Exit Button : **Push Button, Notouch**

(with Wi-Fi)



Realtime RS 20+

- Fingerprint Capacity : **5000**
- Card Capacity : **5000**
- Password Capacity : **5000**
- Attendance logs : **100000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime T304F mini

- Face Capacity : **500**
- Fingerprint Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **100000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime T52F

- Face Capacity : **1000**
- Fingerprint Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **100000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime T501 mini

- Face Capacity : **1000**
- Fingerprint Capacity : **5000**
- Card Capacity : **5000**
- Password Capacity : **5000**
- Attendance logs : **300000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Support Exit Button : **Push Button, Notouch**



Realtime T304F+

- Face Capacity : **1000**
- Fingerprint Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **100000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime RS 910

- Face Capacity : **3000**
- Fingerprint Capacity : **15000**
- Card Capacity : **15000**
- Password Capacity : **15000**
- Attendance logs : **500000**
- Display Size : **4.5 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime RS 70

- Fingerprint Capacity : **3000**
- Card Capacity : **3000**
- Password Capacity : **3000**
- Attendance logs : **100000**
- Display Size : **2.8 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime T28F

- Face Capacity : **1000**
- Card Capacity : **1000**
- Password Capacity : **1000**
- Attendance logs : **100000**
- Display Size : **2.8 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime Pro 304F mini

- Face Capacity : **1500**
- Card Capacity : **1500**
- QR Capacity : **1500**
- Password Capacity : **1500**
- Attendance logs : **150000**
- Display Size : **3.5 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, No touch**



Realtime Pro 304F+

- Face Capacity : **3000**
- Fingerprint Capacity : **3000**
- QR Capacity : **3000**
- Card Capacity : **3000**
- Password Capacity : **3000**
- Attendance logs : **300000**
- Display Size : **4.5 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, No touch**

Supported



Realtime Pro T28F

- Face Capacity : **3000**
- Fingerprint Capacity : **3000**
- QR Capacity : **3000**
- Card Capacity : **3000**
- Password Capacity : **3000**
- Attendance logs : **100000**
- Display Size : **3.0 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, No touch**

Supported



Realtime Pro RS 70

- Face Capacity : **1500/3000**
- Card Capacity : **1500/3000**
- QR Capacity : **1500/3000**
- Password Capacity : **1500/3000**
- Attendance logs : **100000**
- Display Size : **2.6 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, No touch**




Realtime Pro RS 70F

- Face Capacity : **1500/3000**
- Fingerprint Capacity : **1500/3000**
- QR Code : **1500/3000**
- Card Capacity : **1500/3000**
- Password Capacity : **1500/3000**
- Attendance logs : **150000**
- Display Size : **2.6 Inch**
- Access Control : **Yes**
- Wiegand In / Out : **Supported**
- Support Exit Button : **Push Button, Notouch**



Realtime Pro 1100 mini

- Face Capacity : **1500**
- Card Capacity : **1500**
- Password Capacity : **1500**
- Attendance logs : **150000**
- Display Size : **4.0 Inch**
- Access Control : **EM lock, Electric Lock,**
- **Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1100n

- Face Capacity : **2000**
- Card Capacity : **2000**
- QR code : **2000**
- Password Capacity : **2000**
- Attendance logs : **200000**
- Display Size : **4.5 Inch**
- Access Control : **EM lock, Electric Lock,**
- **Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1100b

- Face Capacity : **2000**
- Fingerprint Capacity : **2000**
- QR Code : **2000**
- Card Capacity : **2000**
- Password Capacity : **2000**
- Attendance logs : **200000**
- Display Size : **4.5 Inch**
- Access Control : **EM lock, Electric Lock,**
- **Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1400F

- Face Capacity : **3000**
- Fingerprint Capacity : **3000**
- QR Code : **3000**
- Card Capacity : **3000**
- Password Capacity : **3000**
- Attendance logs : **300000**
- Display Size : **4.5 Inch**
- Access Control : **EM lock, Electric Lock, Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1500F

- Face Capacity : **5000**
- Fingerprint Capacity : **5000**
- QR Code : **5000**
- Card Capacity : **5000**
- Password Capacity : **5000**
- Attendance logs : **500000**
- Display Size : **5.5 Inch**
- Access Control : **EM lock, Electric Lock, Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1600F

- Face Capacity : **10000**
- Fingerprint Capacity : **10000**
- QR Code : **10000**
- Card Capacity : **10000**
- Password Capacity : **10000**
- Attendance logs : **500000**
- Display Size : **7 Inch**
- Access Control : **EM lock, Electric Lock, Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1700F

- Face Capacity : **20000**
- Fingerprint Capacity : **20000**
- QR Code : **20000**
- Card Capacity : **20000**
- Password Capacity : **20000**
- Attendance logs : **500000**
- Display Size : **8.5 Inch**
- Access Control : **EM lock, Electric Lock, Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime Pro 1900F

- Face Capacity : **50000**
- Fingerprint Capacity : **50000**
- QR Code : **50000**
- Card Capacity : **50000**
- Password Capacity : **50000**
- Attendance logs : **500000**
- Display Size : **10.5 Inch**
- Access Control : **EM lock, Electric Lock, Door Sensor, Exit Button, Alarm Output**
- Support Exit Reader : **Push Button, Notouch**



Realtime SFR7 (Slave Reader)

- Basic Configuration : Built-in Proximity / Card Reader
Fingerprint Reader
- Card Type : EM
- Reading Distance : >5Cm
- External Card Reader : Yes
- Operating Voltage : 12V. 2amp
- Unlock Current : 80mA-90mA
- Working Temperature : 0-60°C
- Reading Connectivity : RFID/Finger
- Connectivity : RS 485
- Working devices: T304F+, ProRS70F, Pro304F+, Pro1100n, Pro1100b, Pro1500F, Pro1600F, Pro1700F, Pro1900F




Realtime RS 9+ (Slave Reader)

- Basic Configuration : Built-in Proximity / Card Reader
Fingerprint Reader
- Card Type : EM
- Reading Distance : >5Cm
- External Card Reader : Yes
- Operating Voltage : 12V. 2amp
- Unlock Current : 80mA-90mA
- Working Temperature : 0-60°C
- Reading Connectivity : RFID /Finger
- Connectivity : RS 485
- Working devices: T304F+, ProRS70F, Pro304F+, Pro1100n, Pro1100b, Pro1500F, Pro1600F, Pro1700F, Pro1900F



Realtime T502F mini

- Product Form : **Aadhaar Enable Face recognition**
- Screen Size : **5.5 Inch**
- Battery Backup : **8 Hours**
- Processor : **Octa Core 2.3Ghz**
- Face Recognition : **5MP**
- Fingerprint : **AST 300 L1 Scanner**
- Adapter : **5V 3amp**
- RAM / ROM : **6GB / 64GB**
- Android : **Version 15**




Realtime T502 L1

- Product Form : **Aadhaar Enable Biometric**
- Screen Size : **7 Inch**
- Battery Backup : **8 Hours**
- CPU Speed : **1.5GHz**
- Fingerprint Supplier : **Startek**
- Fingerprint : **FM220U**
- Adapter : **5V 3amp**
- RAM / ROM : **4GB / 64GB**
- Android : **Version 11**




Realtime T502F Plus

- Product Form : **Aadhaar Enable Face recognition**
- Screen Size : **8.5 Inch**
- Battery Backup : **8 Hours**
- Processor : **Octa Core 2.3Ghz**
- Face Recognition : **5MP**
- Fingerprint : **Support All Finger Readers & IRIS**
- Adapter : **5V 3amp**
- RAM / ROM : **6GB / 128GB**
- Android : **Version 15**



Realtime T503F L1

- Product Form : **Aadhaar Enable Face recognition**
- Screen Size : **10.5 Inch**
- Battery Backup : **8 Hours**
- Processor : **Octa Core 2.3Ghz**
- Face Recognition : **5MP**
- Fingerprint : **FM220UL1Scanner**
- Adapter : **12V 3amp**
- RAM / ROM : **8GB / 128GB**
- Android : **Version 15**



Four Door Access Controller

Four Door Access Controller Systems are built on flexible, open technology to provide management, real-time monitoring, and control of your access control system—all from a browser.



Working Mode	Offline / Online
Verification	ID card
Card Capacity (pcs)	30,000
Attendance Record	200,000
Controller to Reader	80-100m Distance
Door Control	4 Door
Communication	TCP / IP
RFID Reader	Support HID, CPU,
Motorola Brand	Reader
Reader Format	WG26/34
Working Humidity	10%-90%
Working Temperature	-40°C – 70°C
Power Supply	12V Dc
Idle Current	4A, 48 watt
Database	Access / SQL
Sound Indicator	Buzzer
Dimension	218 x 106 (mm)



EM Card



Access Control



TCP/IP



RS232/485



All Your Access Control Need Accessories



Push Button Metal Small



L Plate



EM Lock 600 lbs



RIM Locks with RFID
& Remote



Push Button



U Bracket



1200 LBS single Leaf Lock



Strike Lock



Plastic Push Button Big



ZL Bracket



1200 LBS Double Leaf Lock



Power Supply



Plastic Push Button Small



Small Drop Bolt



Drop Bolt



Smart Card



No Touch Push Button



GG Bracket



Glass Door Lock



RF Reader

Realtime TD1D (Standalone)

- Fingerprint Users : 500
- Card User : 500
- Password User : 500
- Fingerprint Verification Mode : 1:1,1:N
- Working Mode : Standalone
- Verification : Fingerprint, ID Card, PIN
- Power Supply : 12V 2amp



Realtime TD1D (FP)

- Face Users : 2000
- Palm User : 1000
- Card User : 2000
- Password User : 2000
- Fingerprint Verification Mode : 1:1,1:N
- Working Mode : Standalone
- Verification : Face, Palm, ID Card, PIN
- Power Supply : 12V 2amp



Realtime T8

- Fingerprint Users : 2000
- Card User : 2000
- Password User : 2000
- Attendance Records : 100,000
- Fingerprint Verification Mode : 1:1,1:N
- Working Mode : Standalone
- Verification : Fingerprint, ID Card, PIN
- Communication : USB, RS 485



Realtime T7

- Fingerprint Users : 1000
- Card User : 1000
- Password User : 1000
- Fingerprint Verification Mode : 1:1,1:N
- Working Mode : Standalone
- Verification : Fingerprint, ID Card, PIN
- Power Supply : 12V 2amp



Realtime ST 25+ (Slave Reader)

- Device Support : T7 / T8
Working : Working with Master Machine
- Power Supply : DC 12V
- Identification Style : Fingerprint / Card
- Identification Speed : <1sec
- FAR : <0.01
- FRR : <0.0001
- Fingerprint Capacity : AS per master device
- Card Capacity : AS per master device
- Communication : RS 485
- Humidity : 20%-60%
- Temperature : 0°C ~ 45°C
- Voice : Buzzer, Dual LED



Realtime K2n / K2s / K9

- Basic Configuration : Built-in Proximity Card Reader and Pin Keyboard
(Keyboard for Management Proximity Card for opening door)
- Card Type : EM
- Reading Distance : >5Cm
- Storage Capacity : 2000 Card or Password
- External Card Reader : No
- Operating Voltage : 12V, 2amp
- Static Current : 65mA-70mA
- Unlock Current : 80mA-90mA
- Lock Type : Relay Output
- Working Temperature : 0-60°C



RFID Card
2000



Password
2000


K2n



K2s



K9



Realtime K7

- Basic Configuration : Built-in Proximity Card Reader and Pin Keyboard
(Keyboard for Management Proximity Card for opening door)
- Card Type : EM
- Reading Distance : >5Cm
- PIN : 1000
- Card : 1000
- External Card Reader : No
- Operating Voltage : 12V, 2amp
- Static Current : 65mA-70mA
- Unlock Current : 80mA-90mA
- Lock Type : Relay Output
- Working Temperature : 0-60°C



RFID Card
500



Password
500



"Realtime Smart"



Realtime RF 10 / RF 10m

- Wiegand 26bits / Wiegand 34bits/ ABA Standard Format Data Output
Less than 0.2 second Response speed
- Less than 0.5 seconds Proximity Time Distance
- 2-15cm Proximity range
- Working Temperature : 0°-60°
- Built-in Antenna
- Built-in LED (Double Color LED)
- Built-in Loud Speaker (Buzzer)
- Proximity Reader 125Khz / Mi fare Reader 13.5Mhz



RF 10 - Proximity
RF 10M - Mi Fare

Controller and UHF

Realtime T4D / T1D

- Working Mode : **Offline / Online**
Verification : **ID Card**
- Card Capacity (PCS) : **30,000**
- Attendance Record : **200,000**
- Controller to Reader : **80-100m Distance**
- Door Control : **4 Door / 1 Door**
- Communication : **TCP / IP**
- RFID Reader : **Support HID, CPU, Motorola Brand Reader**
- Reader Format : **WG26/34**
- Working Humidity : **10%-90%**
- Working Temperature **-40°C-70°C**
- Power Supply : **12V DC**
- Date Base : **Access / SQL**
- Sound Indicator : **Buzzer**

**Four Door
Controller**



**One Door
Controller**



Realtime UHF 10M/ UHF 20M

- Protocol : **ISO 18000-6B, ISO 18000-6C(EPC GEN2)**
- Frequency Range : **Standard ISM 902 ~ 928MHz or ISM 865~868MHz**
other frequency available
- Operation Mode : **FHSS or Fixed frequency (set by software)**
- RF Power : **0~30dBm, software adjustable**
- Reading Speed : **Software Programmable, Average Reading per 64Bits: <6ms**
- Reading Mode : **Timing or touch, Software Programmable**
- Data Ports : Standard : **Wiegand 26/34,**
- Data Input Port : **Trigger Input One Team**
- Antenna : **Built-in line polarization Antenna, Gain : 12 dbi**
- Power Supply : **DC+12V (Power Adapter)**

R500S (10M)



R500B (20M)

Realtime A7 / A9

- Finger Capacity : 500
- Card Capacity : 500
- PIN Capacity : 500
- Identify Mode : **Fingerprint, Card, PIN & Combination**
- Communication : **Wi-Fi**
- APP : **Supported**
- User Validation : **Supported**
- OTP Option : **Yes**
- Working Voltage : **DC5V**
- Working Temperature : **-10°C+50°C**
- Working Humidity (RH) : **20%—80%**
- Self-test function : **Supported**
- Power Management : **Sleep Mode**
- Battery Backup : **Yes**



Download "Realtime Smart"



Realtime GLS 500

- Finger Capacity : 100
- Card Capacity : 200
- PIN Capacity : 300
- Identify Mode : **Fingerprint, Card, PIN & Combination**
- Communication : **Wifi**
- APP : **Supported**
- User Validation : **Supported**
- OTP Option : **Yes**
- Working Voltage : **DC5V**
- Working Temperature : **-10°C+50°C**
- Working Humidity (RH) : **20%—80%**
- Self-test function : **Supported**
- Power Management : **Sleep Mode**
- Battery Backup : **Yes**



Download "Realtime Smart"



Realtime GLS 700

- Finger Capacity : 100
- Card Capacity : 200
- PIN Capacity : 100
- Identify Mode : **Fingerprint, Card, PIN & Combination**
- Communication : **BT**
- APP : **Supported**
- User Validation : **Supported**
- OTP Option : **Yes**
- Working Voltage : **DC5V**
- Working Temperature : **-10°C+50°C**
- Working Humidity (RH) : **20%—80%**
- Self-test function : **Supported**
- Power Management : **Sleep Mode**
- Battery Backup : **Yes**



Download "Realtime Smart"



Smart Door Lock

Realtime GLS 900

- Finger Capacity : **100**
- Card Capacity : **1000**
- PIN Capacity : **1000**
- Identify Mode : **Fingerprint, Card, PIN & Combination**
- Communication : **Wi-Fi**
- APP : **Supported**
- User Validation : **Supported**
- OTP Option : **Yes**
- Working Voltage : **DC5V**
- Working Temperature : **-10°C+50°C**
- Working Humidity (RH) : **20%–80%**
- Self-test function : **Supported**
- Power Management : **Sleep Mode**
- Battery Backup : **Yes**



Download "Realtime Smart"



POE Network Switch

Realtime POE 4 Port 10/100

- 4*10/100Mbps POE Port
- 2*100/100Mbps Uplink Port
- Support : Watchdog,EEE802.3af/at
- Restrain Network Storm
- VLAN Function
- Power Supply : 220V AC



Realtime POE 8 Port 10/100

- 8*10/100Mbps POE Port
- 2*10/100Mbps Uplink Port
- Support : Watchdog,IEEE802.3af/at
- Restrain Network Storm
- VLAN Function
- Power Supply : 220V AC




Realtime POE 4 Full Giga with SFP

- 4*10/100/1000Mbps POE Port
- 2*10/100/1000Mbps Uplink Port
- 1*1000Mbps SFP Slot
- Support : Watchdog,IEEE802.3af/at
- Restrain Network Storm
- VLAN Function
- Power Supply : 220V AC



Realtime POE 8 Full Giga with SFP

- 8*10/100/1000Mbps POE Port
- 2*10/100/1000Mbps Uplink Port
- 1*1000Mbps SFP Slot
- Support : Watchdog,IEEE802.3af/at
- Restrain Network Storm
- VLAN Function
- Power Supply : 220V AC



Realtime POE 16 Full Giga with SFP

- 16*10/100/1000Mbps POE Port
- 2*10/100/1000Mbps Uplink Port
- 1*1000Mbps SFP Slot
- Support : Watchdog,IEEE802.3af/at
- Restrain Network Storm
- VLAN Function
- Power Supply : 220V AC



Realtime 4G/5G Internet Router

Realtime W8+ (Three Antenna)

- 1 LAN Port
- Wi-Fi
- 4G/5G (All SIM Support)
- Three Antenna Router
- USB Power Cable
- High Speed Internet
- Led Indicator



Realtime RSMD1 (Single Zone)

- LED light bars on both door panels
- 190 LED's on both panels
- 1 pin point zone to precisely identify locations from head to toe.
- Auto set, Micro Controller Based
- High Performance Detection
- Operational Frequency can be adjusted
- Manually or automatically
- Sensitivity setting of individual zones 0-400
- Frequency level 0-50
- Audio / Visual indications for metal detection
- WALK-STOP indicators to regulate the flow of traffic
- Easy to mount / assemble



Realtime RSMD3 (Three Zone)

- LED light bars on both door panels
- 190 LED's on both panels
- 3 pin point zone to precisely identify locations from head to toe.
- Auto set, Micro Controller Based
- High Performance Detection
- Operational Frequency can be adjusted
- Manually or automatically
- Sensitivity setting of individual zones 0-400
- Security level 0-200
- Frequency level 0-50
- Audio / Visual indications for metal detection
- WALK-STOP indicators to regulate the flow of traffic
- Easy to mount / assemble



Realtime RSMD9 (Nine Zone)

- LED light bars on both door panels
- 190 LED's on both panels
- 9 pin point zone to precisely identify locations from head to toe.
- Auto set, Micro Controller Based
- High Performance Detection
- Operational Frequency can be adjusted
- Manually or automatically
- Sensitivity setting of individual zones 0-400
- Security level 0-200
- Frequency level 0-50
- Audio / Visual indications for metal detection
- WALK-STOP indicators to regulate the flow of traffic
- Easy to mount / assemble



Realtime RSMD18 (Eighteen Zone)

- LED light bars on both door panels
- 190 LED's on both panels
- 18 pin point zone to precisely identify locations from head to toe.
- Auto set, Micro Controller Based
- High Performance Detection
- Operational Frequency can be adjusted
- Manually or automatically
- Sensitivity setting of individual zones 0-200
- Security level 0-200
- Frequency level 0-90
- Audio / Visual indications for metal detection
- WALK-STOP indicators to regulate the flow of traffic
- Easy to mount / assemble



Realtime RSMD18W

- 06/12/18 Zones to precisely identify locations horizontally and vertically from head to toe.
- Touch LCD Display for better visualization
- Operating frequency (0~99), with adaptive function
- According to the working environment
- Alarm time can be adjusted
- Sensitivity Level : 0~400
- Security Level : 0-100
- IN/OUT & alarm counter : 0-999999
- Zone detection shows LED indication on both side (left & right) of DFMD
- LCD display on panel indicating volume of metal upto 18 stages
- Detect all types of metal
- Password protected for better security
- Harmless to human body (Heart Pacemaker, Pregnant women) Magnetic Floopy, recording Tape etc),
- Battery Backup and Ramp over (Optional)



Additional Specification

- Screen Brightness setting, screen sleep setting
- Date and time setting
- Password 1 to 8 digit (numeric)
- LCD screen shown human body display for metal location
- Interference shown in display
- Scene setting 85 places
- Line cable (port & software) optional

Realtime RSMD330

- 11/22/33 Zones to precisely identify locations horizontally and vertically from head to toe.
- Operating frequency can be adjusted manually or automatically working frequency (0-99), with adaptive function
- According to the working environment
- Multi-alarm sound to choose. (Different Sound)
- Alarm time can be adjusted
- Sensitivity Level : 0-400
- Security Level : 0-99
- Alarm & Pass Counter : 0-999999
- Zone detection shows LED indication on both sides (left & right) of DFMD
- LED bar on panel indicating density of metal upto 300 stages



Realtime RSM109SD

- 6 Zones to precisely identify locations horizontally on both sides uniformly (left & right) from head to toe.
- Operating frequency can be adjusted manually or automatically working frequency (0-99), with adaptive function
- According to the working environment
- Multi-alarm sound to choose. (Different Sound)
- Alarm time can be adjusted
- Sensitivity Level : 0-400
- Security Level : 0-255
- Alarm & Pass Counter : 0-999999
- Zone detection shows LED indication on both sides (left & right) of DFMD
- LED bar on panel indicating density of metal upto 300 stages
- Detect all types of metal
- Password protected for better security
- Harmless to human body (Heart Pacemaker, Pregnant Women)
- Magnetic Floppy, recording tape etc
- Battery Backup and Ramp over (Optional)




Realtime RSM109SD

- Single Push to ON
Super high sensitivity, Detect all type of metals
- Audio, visual & Vibration alarm
Visual indication for "ON", "METAL", LED indication
- Operate of 1.5V Rechargeable and Alkaline battery
- Sensitivity high/ Medium / Low Button
- Gives continual sound on alarm or vibration if the battery is low



Realtime Boom Barrier DC Power

- Machine Size : **330*260*1050 (mm)**
- Output Input Voltage : **220V**
- Steel Plate thickness : **1.8mm(2.0mm)**
- Motor Speed : **1000r/min**
- **Opening Speed : 5 Sec**
- Motor Shaft height : **830mm**
- Working Voltage : **DV24/10A**
- Control Input : **Support 485, TCP**
- Working Temperature : **-25°+60°**
- Color : **Gold/Black**
- External Power Source : **220V 50/60HZ**



Realtime Boom Barrier DC Power

- Machine Size : **330*260*1050 (mm)**
- Output Input Voltage : **220V**
- Steel Plate thickness : **1.8mm(2.0mm)**
- Motor Speed : **1200r/min**
- **Opening Speed : 3 Sec**
- Motor Shaft height : **830mm**
- Working Voltage : **DV24/10A**
- Control Input : **Support 485, TCP**
- Working Temperature : **-25°+60°**
- Color : **Gold/Black**
- External Power Source : **220V 50/60HZ**



Realtime Boom Barrier DC Power

- Machine Size : **320*260*900 (mm)**
- Output Input Voltage : **220V**
- Steel Plate thickness : **1.5mm (non standard)**
- Motor Speed : **1800r/min**
- **Opening Speed : 1 Sec**
- Motor Shaft height : **830mm**
- Working Voltage : **DV24/10A**
- Control Input : **Support 485, TCP**
- Working Temperature : **-25°+60°**
- Color : **Gold/Black**
- External Power Source : **220V 50/60HZ**



Smart Home Camera 360

Realtime Camera C7 / C7 mini

- Camera Quality : 3MP / 2MP
- Image Sensor : 1/3" 2MP CMOS Image sensor
- Min Illumination : 0.01 lux
- Frame Rate : 20fps
- IR Cut : Supported
- Body Material : Polycarbonate
- Audio : Two Way Audio
- Motion Detection : Yes
- Motion Tracking : Yes
- SD Card Upto 128 GB



Outdoor Smart Wifi / 4G Camera

Realtime Camera C8 / C8+

- Camera Quality : 3MP
- Image Sensor : 1/3" 2MP CMOS Image sensor
- Min Illumination : 0.01 lux
- Frame Rate : 20fps
- IR Cut : Supported
- Body Material : Polycarbonate
- Audio : Two Way Audio
- Motion Detection : Yes
- Motion Tracking : Yes
- SD Card Upto 256 GB



Solar 4G Smart Camera

Realtime Camera C9 eco plus

- Camera Quality : 4MP
- Video Compression Standard : H.264+ / H.265 / H.265+
- Infrared LED : 6 LED
- Infrared IR Distance : 30 meters
- Light Mode : Full Color / Infrared
- Alarm : Motion Detection, Human Detection
- Storage : SD Card 256GB
- Solar Panel : 9W
- Body : Polycarbonate
- Power Input : 5V, 2amp



Realtime Camera C7 B4G

- Camera Quality : 4MP
- Image Sensor : 1/3" 2MP CMOS Image sensor
- Min Illumination : 0.01 lux
- Frame Rate : 20fps
- IR Cut : Supported
- Body Material : Polycarbonate
- Light Mode Full Color / Infrared / Intelligent
- On Screen Display : Date, Time & Title
- Slot : 4G SIM Card / Micro SD Card
- Storage : SD 256GB
- Cloud Storage : Yes (Optional)
- Connection Mode : 4G SIM Network / Lan Network



Realtime Camera C7 D4G

- Camera Quality : 4MP
- Image Sensor : 1/3" 2MP CMOS Image sensor
- Min Illumination : 0.01 lux
- Frame Rate : 20fps
- IR Cut : Supported
- Body Material : Polycarbonate
- Light Mode Full Color / Infrared / Intelligent
- On Screen Display : Date, Time & Title
- Slot : 4G SIM Card / Micro SD Card
- Storage : SD 256GB
- Cloud Storage : Yes (Optional)
- Connection Mode : 4G SIM Network / Lan Network



4G/5G Outdoor with Dual Lens

Realtime Camera C8 Dual Lens

- Camera Quality : 4MP
- Image Sensor : 1/3" 2MP CMOS Image sensor
- Min Illumination : 0.01 lux
- Frame Rate : 20fps
- IR Cut : Supported
- Body Material : Polycarbonate
- Light Mode Full Color / Infrared / Intelligent
- On Screen Display : Date, Time & Title
- Slot : 4G SIM Card / Micro SD Card
- Storage : SD 256GB
- Cloud Storage : Yes (Optional)
- Connection Mode : 4G SIM Network / Lan Network



Canteen Management System with FACE WITH FINGERPRINT

- Order Management ●
- Cashless Transactions ●
- Inventory Management ●
- Billing and Invoicing ●
- Multi-Location Management ●




Specifications

» Authentication	Face, Finger, RFID Card(125 KHz), MiFare(Optional)
» Fingerprint Sensor	Optical
» Face Capacity	1000
» Fingerprint Capacity	1000
» Card Capacity	1000
» Password Capacity	1000
» Template Standard	ISO 19794-2
» Resolution & Image Size	500 dpi & 272x320(pixel)
» Fingerprint Sensor Area	16 x 19 mm
» Fingerprint Verification	1:1, 1:N
» Fingerprint Recognition	<1 second
» Punch Capacity	100000
» Employee Capacity	1000 (20,000 Optional)
» Display	128 x 64 Graphic LCD with Backlight
» Keyboard	5 x 3 Numeric & Function Keys
» Indicator	LED for ON, OK & Error With Voice
» Connectivity	TCP/IP & USB Disk
» Mounting	Table Top & Wall Mount
» Power Input	220V AC

Desktop Attendance Solution

A complete offline solution designed for organizations to manage
ATTENDANCE, LEAVE, AND PAYROLL



SINGLE USER

For standalone usage on one system

Multi User (LAN Based)


Multiple users can access and manage data within the same network.

Solutions :

- **Attendance Management** – Track employee in/out time, shift, and overtime.
- **Leave Management** – Manage different types of leave (CL, SL, PL, etc.) with balance tracking.
- **Payroll Management** – Auto-generate salary with customizable formulas (basic, HRA, allowances, deductions).
- **Reports & Export** – Generate detailed MIS reports, attendance sheets, salary slips, and export data to Excel/PDF.
- **Device Integration** – Compatible with biometric attendance devices for real-time data sync.

Desktop Multi-location


Attendance & Payroll Solution




Key Features :

- **Multi-Location Support** – Centralized management of attendance and payroll for all branches.
- **Shift & Scheduling** – Create, assign, and manage multiple shifts and rosters easily.
- **Leave Management** – Track and approve leaves with configurable leave policies.
- **Payroll Processing** – Auto-generate salary slips with tax, PF, ESI, overtime, allowances, and deductions.
- **Reports & Analytics** – Detailed branch-wise reports for attendance, leave, and salary.

MULTI LOCATION ATTENDANCE SOLUTION with Mobile APP (Web/Cloud)



Admin Check Office Attendance on APP



Cloud Server



Employee Realtime Attendance Through APP

FIELD STAFF TRACKING

NOTIFICATION

Cloud Server

LEAVE REQUEST

SELF ATTENDANCE

GEO FENCING

LEAVE APPROVAL

REPORT CHECK

CHAT WITH ADMIN

PARKING MANAGEMENT

Face recognition, UHF Reader, ANPR

ANPR
CAMERA





Name : Dheeraj ✓
Vehicle No : DL1A52656
Face ID : 00007
Fasttag ID : 125366595955



NUMBER PLATE

REALTIME SMART PARKING

Parking Management Software

ADVANCING IDENTITY VERIFICATION


- Manage resident card database
- Guest entry pre-registration
- Car entry through FAST TAG/ RFID TAG / Card Number
- Validity for tenant
- Block / Unblock for Vehicle
- Chargeable / Free Vehicle Entry
- Unlimited Entry / Exit point management



CAR PARKING | APARTMENTS | MALLS PARKING | SCHOOL PARKING | GOVERNMENT OFFICES

PARKING MANAGEMENT SYSTEM

The Key to a Secure & Efficient Workplace




The solution supports real-time slot availability, automated ticketing, online payments, and multi-location management, making it ideal for malls, offices, residential complexes, airports, and public parking areas.

Key Features :

- **Automated Entry/Exit** – Integration with RFID, ANPR (Automatic Number Plate Recognition), or Barcode for seamless vehicle access.
- **Smart Ticketing** – Paperless ticket generation (QR code / digital pass).
- **Real-Time Space Availability** – Live view of occupied and free slots.
- **Multi-Location Support** – Centralized monitoring of multiple parking sites.
- **Payment Integration** – Cash, Card, UPI, Wallet, and Online Payment gateway support.
- **User-Friendly Dashboard** – Centralized control panel for admins and operators
- **Reporting & Analytics** – Revenue reports, occupancy trends, peak hours, and audit trails.

VISITOR MANAGEMENT SYSTEM

The Key to a Secure & Efficient Workplace



VISITOR REGISTRATION

FROM WITH VISITOR PASS WITH VISITOR PHOTO

QUICK VISITOR SIGN
OUT OPTION

DAILY VISITOR
ENTRY/EXIT REPORT

MONTHLY VISITOR
ENTRY/EXIT REPORT


WHATS APP & SMS
INTEGRATION FEATURE.

QR OPTION AVAILABLE
FOR VISITOR ENTRY.

VISITOR CARD VALIDITY
OPTION FOR ACCESS CONTROL

VISITOR MANAGEMENT SYSTEM

The Key to a Secure & Efficient Workplace



Visitor management software typically includes several key features to streamline the process of managing visitors in offices, schools, hospitals, or other facilities.

Visitor Management Software Benefits

Improved Efficiency:

- Reduces manual tasks and wait times.

Enhanced Security:

- Tracks and verifies visitors in real-time for better control.

Data Insights:

- Helps analyse visitor trends and improve operations.

Scalability:

- Accommodates businesses of all sizes and industries.


Integration with
Access Control

Multi-Location
Support

Enhanced Security

"Transform Your Gym"

with Our All-In-One Gym Management Software



KEY FEATURES


- ★ Attendance Tracking
- ★ Billing and Payment Processing
- ★ Reporting and Analytics
- ★ Integration with Access Control System
- ★ Whats APP & SMS Notification Available

Model : RS 9w



"Transform Your Gym"

with Our All-In-One Gym Management Software



KEY FEATURES

Gym management software is designed to streamline operations, improve member engagement, and enhance overall efficiency for gyms and fitness centers.

MEMBERSHIP
MANAGEMENT

BILLING AND PAYMENT
PROCESSING

CLASS AND SCHEDULE
MANAGEMENT

STAFF
MANAGEMENT

WORKOUT AND
PROGRESS TRACKING

MOBILE APP
SUPPORT

REPORTING AND
ANALYTICS

ACCESS CONTROL

MULTI-LOCATION
MANAGEMENT



Realtime Worldwide



Realtime Biometrics India (P) Limited

C-83, Ganesh Nagar Pandav Nagar Complex, Delhi-110092 INDIA

e-mail: info@realtimebiometrics.com

www.realtimebiometrics.com

Contact US : +91- 8860 8860 86

Factory : E1 ,E2,E3, UPSIDC Industrial, Gajraula

Factory : D-166,167 Sector-80, Noida